




BIMA 1

spot for 240V 3-phase track, single-headed, QPAR51,- round, matt white, max. 50W, incl. 3-phase adapter

Adjustable high-voltage spot BIMA 1 with suitable adapter for the 240V 3-phase track system. The luminaire is made of aluminium and, thanks to the GU10 socket, is suitable for both halogen and LED lamps.



TECHNICAL DATA

| | |
|---------------------------|-------------------------|
| Item no. | 152241 |
| Socket | GU10 |
| Number of sockets | 1 |
| Tilt range | 200 ° |
| Horizontal rotation range | 350 ° |
| Rotating or tilting | rotary Bar and tiltable |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling,Track Ceiling |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Safety class | II |
| Wattage | 50 W |
| Color | white |
| Light outlet | direct |
| Length | 8 cm |
| Height | 15 cm |
| Diameter | 6 cm |
| Net weight | 0.297 kg |
| Gross weight | 0.36 kg |
| BIG WHITE Page | 541 |

Recommended lamp

| | |
|---------|--|
| 1005273 | QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36° |
| 1005079 | LED lightbulb QPAR51 , GU10, 3000K, white |
| 1005076 | LED lightbulb QPAR51 , GU10, 2700K, white |
| 1005082 | LED lightbulb QPAR51 , GU10, 4000K, white |