




KARPO

recessed fitting, single-headed, LED, 3000K, black, flat canopy, 7.5W

KARPO series lights are available in white and black. It has a spot in a cylindrical shape which can be individually aligned via the hinge on the flat canopy. The swivel and tilting range allows you to optimally light up the room. The integrated premium LEDs provide high energy efficiency. In addition, the luminaire has a high colour rendering index of over 90. To operate, the single-headed FRAME Spots needs a suitable constant current driver rated at 500mA.



TECHNICAL DATA

Item no.	152380
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling,Wall
Secondary power / voltage	500 mA
Safety class	III
Wattage	7.5 W
Maximum ambient temperature	40 °C
Lumen	450 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	black
CRI	90
LXXBXX data	L70B50
Service life	30000 h
Light distribution	rotational symmetric
Light outlet	direct
Length	15.2 cm
Height	5.5 cm
Diameter	3 cm
Net weight	0.175 kg

Light Source

916381	
--------	---

Gross weight	0.278 kg
Shape of cut-out	round
Installation depth	2 cm
Installation diameter	7 cm
BIG WHITE Page	232