




HELIA

wall and ceiling light, single-headed, LED, 3000K, 35°, white


The functional HELIA wall and ceiling light consists of an aluminium structure that is optionally available with a black or white housing. The lamp head can also be rotated and swivelled. Thanks to the built-in Premium LED, the single-headed HELIA luminaire is ready for direct connection to the 230V mains power supply.



TECHNICAL DATA

Item no.	156501
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Level of inrush current	10 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.02
Lumen	820 lm
Colour temperature	3000 Kelvin
Beam angle	35 °
Color	white
CRI	90
LXXBXX data	L70B50

Light Source

916387		Service life	30000 h
		Width	9 cm
		Height	9.5 cm
		Depth	12 cm
		Net weight	0.439 kg
		Gross weight	0.576 kg