


TRUST 60

outdoor floor stand, LED, 3000K, IP55, stainless steel 316, Ø/H 6/60 cm, 8.6W

With the stainless steel TRUST 60 floor stand, the opalescent PC light surface is enclosed by a stainless steel cap. With protection class IP55, it is suitable for outdoor use. As an option an earth spike as well as a connection box for safe electrical connection to the round luminaire upright, are available. The electrical connection of the luminaire, which comes in two sizes, is directly to the 230V mains supply. A stainless-steel grid is available as a further accessory to change the lighting effect. The TRUST series contains other wall lights and can therefore be used universally. This luminaire is fitted with a powerful 8.6W LED.



TECHNICAL DATA

Item no.	228110
Number of different light outlets	1
IP Code	IP 55
Impact resistance class	IK 07
Impact resistance	2 Joule
Assembly	Surface
Assembly details	Ground
Primary nominal voltage	220-240V ~50/60Hz
Safety class	I
Wattage	9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Stroboscopic effect (SVM)	3.25
Lumen	400 lm
Colour temperature	3000 Kelvin
Color	stainless steel
CRI	80
LXXBXX data	L70B50
Service life	35000 h
Light distribution	rotational symmetric
Light outlet	direct - indirect
Height	60.5 cm

Light Source

709322	
--------	---

Accessories

228130	GRID 316 , for TRUST outdoor floor stand, stainless steel 316
228730	CONNECTION BOX , 3-pin, IP68
227922	EARTH SPIKE , for TRUST, NAILS, BIG NAILS, BIG NAILS PLUS and ENERGY PACK, length 50cm
1000449	GRID for Trust stainless steel

Diameter	6 cm
Net weight	2.716 kg
Gross weight	3.094 kg
BIG WHITE Page	667