
Specialist • Lighting • Vendor







DASAR FLAT80

outdoor inground fitting, LED, 3000K, IP67, round, brushed stainless steel, 3.5W

The DASAR FLAT LED 230 V recessed ground light is the high-voltage recessed ground light from SLV thatcan be walked on and impresses with its stainless steel screen and glass cover in a partial satin finish. Then there is the high-quality housing made of 304 stainless steel and glass. See the outdoor lights in action and let yourself be impressed by a stunning lighting experience.

TECHNICAL DATA

Item no.	228412
IP Code	IP 65 / IP 67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground,Wall
Mechanical loading	0.5 t
Primary nominal voltage	220-240V ~50/60Hz
Safety class	I
Wattage	3.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Temperature at glass (light emission)	56 °C
Stroboscopic effect (SVM)	0.45
Lumen	140 lm
Colour temperature	3000 Kelvin
Color	stainless steel
CRI	80
LXXBXX data	L70B50
Service life	30000 h
Risk Group	0
Height	6 cm

Specialist • Lighting • Vendor



Light Source

954794	Å F
Accessories	
228730	CONNECTION BOX , 3-pin, IP68

Diameter	8 cm
Net weight	0.431 kg
Gross weight	0.471 kg
Shape of cut-out	round
Installation depth	5.7 cm
Installation diameter	6.6 cm
BIG WHITE Page	839