
# Specialist • Lighting • Vendor








## **HELIA**

outdoor pathway and floor stand, LED, 3000K, round, anthracite, 15W, can be converted to a spike luminaire

The HELIA LED pathway luminaire is fitted with a powerful 15W high-voltage LED and comes in a warm-white colour of light. The luminaire is made of aluminium and is connected using the 3m supply cable with open cable ends directly to the 230V mains supply. Thanks to its IP55 protection class, the luminaire is suitable for outdoor use. This dimmable luminaire contains built-in LED lamps.



#### **TECHNICAL DATA**

Item no.	228555
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 66
Impact resistance class	IK 04
Impact resistance	0.5 Joule
Assembly	Surface
Assembly details	Ceiling, Ground, Ground with Acc., Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	15 W
Level of inrush current	10 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.07
Lumen	1340 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	anthracite
CRI	80
LXXBXX data	L70B50
	•

# Specialist • Lighting • Vendor



## Light Source

916476	E	
Accessories		
228560	EARTH SPIKE , for HE- LIA pathway and floor stand, stainless steel, 17 cm	

Service life	40000 h
Length	16.2 cm
Height	15 cm
Diameter	10 cm
Net weight	1.342 kg
Gross weight	1.525 kg
BIG WHITE Page	699