




DASAR 225

outdoor inground fitting, LED, 4000K, IP67, stainless steel 316, asymmetrical, 34W


The high-voltage inground light DASAR 225 LED SQUARE inground light is accessible and impresses with its stainless steel screen and glass cover in a partial satin finish. Its IP 67 protection class makes it ideal for outdoor use. The rotatable and pivoting GU10 fitting allows flexible alignment of the light cone. In this way, the outdoor inground light LED creates an exciting lighting atmosphere that convinces with a long LED lifespan of 25,000 hours. Experience the outdoor lights in action and convince yourself of an all-round successful lighting experience.



TECHNICAL DATA

Item no.	229381
IP Code	IP 65 / IP 67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Mechanical loading	2 t
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	750 mA
Safety class	I
Wattage	31 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	18.6 A
Duration of inrush current	240 µs
Temperature at glass (light emission)	41 °C
Stroboscopic effect (SVM)	0.01
Lumen	1720 lm
Colour temperature	4000 Kelvin
Color	stainless steel
CRI	90
LXXBXX data	L70B50

Light Source

791825	
Service life	50000 h
Length	25.5 cm
Width	25.5 cm
Depth	14.5 cm
Net weight	5.93 kg
Gross weight	6.439 kg
Shape of cut-out	square
Installation length	24.5 cm
Installation width	24.5 cm
Installation depth	17.5 cm
BIG WHITE Page	839