



BRICK DOWNUNDER


outdoor recessed wall light, LED, 3000K, IP54, rectangular, silver-grey

Made from aluminium and equipped with powerful SMD LED recessed wall luminaire with indirect, glare-free light output. Rated IP54 it is suitable for outdoor use. Available in different colour versions, the electrical connection is made directly to 230V mains supply. For simplified mounting, a suitable installation housing is included. This luminaire contains built-in LED lamps.

TECHNICAL DATA

Item no.	229702
IP Code	IP 54
Assembly	Recessed
Assembly details	Wall
Primary nominal voltage	220-240V ~50/60Hz
Safety class	I
Wattage	1.4 W
Ambient temperature	25 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Stroboscopic effect (SVM)	0.23
Lumen	30 lm
Colour temperature	3000 Kelvin
Color	grey
CRI	80
LXXBXX data	L70B50
Service life	20000 h
Width	17 cm
Height	10.5 cm
Depth	7 cm
Net weight	0.847 kg
Gross weight	0.937 kg

Light Source

916533		Shape of cut-out	square
		Installation length	10 cm
		Installation width	16 cm
		Installation depth	7.5 cm
		BIG WHITE Page	827