




## IPERI 50

outdoor floor stand, LED, 4000K, IP44, anthracite, 48 LED, L/W/H 17.4/12.7/50.2 cm

The square aluminium IPERI 50 floor stand is fitted with a large number of powerful SMD LEDs. With protection class IP44, it is suitable for outdoor use. The different colour versions available are supplied with connection box for simplified installation. An earth spike is available as an option. In addition, the installation can be extended by wall lights of the series.



## TECHNICAL DATA

Item no.	231305
IP Code	IP 44
Impact resistance class	IK 02
Assembly	Surface
Assembly details	Ground
Primary nominal voltage	220-240V ~50/60Hz
Safety class	II
Wattage	4.5 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	40 °C
Stroboscopic effect (SVM)	0.03
Lumen	400 lm
Colour temperature	4000 Kelvin
Beam angle	100 °
Color	anthracite
CRI	80
LXXBXX data	L70B50
Service life	25000 h
Length	12.7 cm
Width	17.4 cm
Height	50.2 cm
Net weight	1.579 kg

Light Source

916413	
--------	---

Gross weight	2.014 kg
--------------	----------

Accessories

BIG WHITE Page	681
----------------	-----

231231	EARTH SPIKE , for IPE-RI, galvanised steel, length 50cm incl. bolts
--------	---