




DASAR® 920

LV, LED outdoor inground fitting, LED, 3000K, IP67, round, bezel brushed stainless steel, 12-25V, 6.5W

The high-voltage DASAR LED LV recessed ground light can be walked on and impresses with its stainless steel screen and glass cover in a partial satin finish. In this way, the outdoor LED recessed ground light creates an exciting lighting atmosphere that impresses with a long LED life-span of 25,000 hours. Experience light with SLV – your innovative partner for all kinds of outdoor lighting for 40 years.



TECHNICAL DATA

Item no.	233500
IP Code	IP 67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Mechanical loading	1 t
Primary nominal voltage	12-24V
Safety class	III
Wattage	6.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Temperature at glass (light emission)	44.8 °C
Stroboscopic effect (SVM)	0
Lumen	520 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	stainless steel
CRI	80
LXXBXX data	L70B50
Service life	25000 h
Depth	6 cm

Light Source

954802	
--------	---

Accessories

1005444	LED Power supply , 15W 12V
1005445	LED Power supply , 15W 24V

Diameter	9.2 cm
Net weight	0.591 kg
Gross weight	0.689 kg
Shape of cut-out	round
Installation depth	10.2 cm
Installation diameter	8.2 cm
BIG WHITE Page	840