



## DASAR® 920

HV, LED outdoor inground fitting, LED, 3000K, IP67, round, bezel brushed stainless steel, 230V, 5,6W

The DASAR LED HV recessed ground light can be walked on and impresses with its stainless steel screen and glass cover in a partial satin finish. In this way, the outdoor LED recessed ground light creates an exciting lighting atmosphere that impresses with a long LED lifespan of 25,000 hours. Experience light with SLV – your innovative partner for all kinds of outdoor lighting for 40 years.

### TECHNICAL DATA

|                                       |                      |
|---------------------------------------|----------------------|
| Item no.                              | 233520               |
| IP Code                               | IP 67                |
| Impact resistance class               | IK 08                |
| Impact resistance                     | 5 Joule              |
| Assembly                              | Recessed             |
| Assembly details                      | Ground               |
| Mechanical loading                    | 1 t                  |
| Primary nominal voltage               | 220-240V ~50/60Hz    |
| Secondary power / voltage             | 400 mA               |
| Safety class                          | I                    |
| Wattage                               | 5.5 W                |
| Maximum ambient temperature           | 40 °C                |
| Temperature at glass (light emission) | 44.8 °C              |
| Lumen                                 | 300 lm               |
| Colour temperature                    | 3000 Kelvin          |
| Beam angle                            | 40 °                 |
| Color                                 | stainless steel      |
| CRI                                   | 80                   |
| LXXBXX data                           | L70B50               |
| Service life                          | 25000 h              |
| Light distribution                    | rotational symmetric |
| Light outlet                          | direct               |

Light Source

|        |   |
|--------|---|
| 916428 |  |
|--------|---|

|                       |          |
|-----------------------|----------|
| Depth                 | 9.4 cm   |
| Diameter              | 9.2 cm   |
| Net weight            | 0.704 kg |
| Gross weight          | 0.788 kg |
| Shape of cut-out      | round    |
| Installation depth    | 10.2 cm  |
| Installation diameter | 8.2 cm   |
| BIG WHITE Page        | 840      |