




# Q-LINE PD

**LED Indoor pendant light, 2 m, BAP, black, 4000 K**

The Q-LINE ceiling light is optionally available with a white, black, or silver-grey luminaire housing. It is also available with a pure white or warm white LED, and different dimensions. Its high luminance and UGR value of less than 10 make the Q-Line luminaire suitable for workstations. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1000936 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP20 |
| **Dimmable** | Yes |
| **Dimming technology** | trailing edge |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 900 mA |
| **Safety class** | I |
| **Wattage** | 93 W |
| **Level of inrush current** | 30 A |
| **Duration of inrush current** | 40 µs |
| **Lumen** | 4600 lm |
| **Colour temperature** | 4000 Kelvin |
| **Beam angle** | 30 ° |
| **Color** | black |
| **CRI** | 90 |
| **UGR ≤** | 10 |
| **Service life** | 25000 h |
| **Length** | 200 cm |
| **Width** | 6 cm |
| **Height** | 6 cm |
| **Pendant length** | 150 cm |

| | |
|---|---|
| 916460 |  |

| | |
|---|---|
| **Net weight** | 4.593 kg |
| **Gross weight** | 5.278 kg |
| **BIG WHITE Page** | 295 |