





MEDO 60 EL

LED indoor recessed ceiling light, frameless version, white, 3000/4000K

The recessed version of the MEDO series fits into every room concept seamlessly thanks to its understated design. The MEDO Frameless combines with the ceiling in a charming way. The light colour can be easily switched between 3000K and 4000K prior to installation using a switch. The integrated premium LED module provides an even lighting effect. Supplemented by an additional driver, the TRIAC recessed variant becomes dimmable and can be integrated in DALI systems.



TECHNICAL DATA

Item no.	1001903
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	1000/1050 mA
Safety class	III
Wattage	36 W
Maximum ambient temperature	40 °C
Lumen	4700/5000 lm
Colour temperature	3000/4000 Kelvin
Beam angle	105 °
Color	white
CRI	80
UGR ≤	25
LXXBXX data	L70B50
Service life	25000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	12.5 cm
Diameter	60 cm
Net weight	5.257 kg

916477	

Accessories

1005387	LED Driver , 40W 1000-mA PHASE
1006120	LED driver , 40W 700/900/1000mA
1004782	LED driver , 31.5-44W 800/900/1050mA
1006197	LED driver , 40W 1050-mA DALI dimmable with RF interface LED driver white DALI
1002424	LED driver MEDO 400 , dimmable DALI/1-10V
464804	LED DRIVER , 40W, 1050mA, triac dimmable

Gross weight	7.146 kg
Shape of cut-out	round
Installation depth	16 cm
Installation diameter	61 cm
BIG WHITE Page	170