




1~ KALU TRACK

Indoor LED 1-circuit system luminaire, black, 3000 K, including 1-circuit adapter

Adjustable KALU TRACK spotlight with suitable adapter for the 1-circuit 240V track system. Designed as an extension of the popular KALU series, this new track-mounted spotlight takes on the shape of the product family. The incorporated LED module guarantees high light output with low electricity consumption. To meet all lighting requirements, versions with G53 and GX53 sockets for the 1- and 3-circuit systems are also available. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1002854
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Safety class	II
Wattage	13 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	3 A
Duration of inrush current	10 µs
Lumen	970 lm
Colour temperature	3000 Kelvin
Beam angle	95 °
Color	black
CRI	80
Service life	25000 h
Length	12 cm
Height	15 cm
Diameter	10.5 cm

703130	

Net weight	0.448 kg
Gross weight	0.54 kg
BIG WHITE Page	581