

# PANEL 60 DALI

**Indoor LED surface-mounted ceiling lights round white 4000K**

The PANEL 60 DALI ceiling light is available in several different light colours and impresses with its ultra-flat design and powerful, dimmable LED modules. The aluminium frame is fitted with an acrylic glass cover which provides homogeneous and glare-free illumination. The built-in DALI-compatible operating device makes direct connection to a mains power supply of 100V - 240V possible.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1003041 |
| **IP Code** | IP 20 |
| **Assembly** | Surface |
| **Assembly details** | Ceiling |
| **Dimmable** | Yes |
| **Dimming technology** | DALI |
| **Number of through-wires** | 40 |
| **Primary nominal voltage** | 120-277V ~50/60Hz |
| **Secondary power / voltage** | 1000 mA |
| **Safety class** | I |
| **Wattage** | 43 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Network rated standby power** | 0.3 W |
| **Level of inrush current** | 30 A |
| **Duration of inrush current** | 30 µs |
| **Stroboscopic effect (SVM)** | 0.02 |
| **Lumen** | 3350 lm |
| **Colour temperature** | 4000 Kelvin |
| **Beam angle** | 110 ° |
| **Color** | white |
| **CRI** | 80 |

| | |
|---|---|
| 916481 |  |

| | |
|---|---|
| **UGR ≤** | 22 |
| **LXXBXX data** | L70B50 |
| **Service life** | 30000 h |
| **Height** | 5.5 cm |
| **Diameter** | 60 cm |
| **Net weight** | 4.673 kg |
| **Gross weight** | 5.877 kg |
| **BIG WHITE Page** | 275 |