


# PANEL DALI

**Indoor LED surface-mounted ceiling lights 1200x300 mm white 3000 K**

The PANEL DALI pendant, which is available in several different light colours, impresses with its ultra-flat design and powerful, dimmable LED modules. The aluminium frame is fitted with an acrylic glass cover which provides homogeneous and glare-free illumination. The built-in DALI-compatible operating device makes direct connection to a mains power supply of 100V-240V possible.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1003052 |
| **IP Code** | IP20 |
| **Dimmable** | Yes |
| **Dimming technology** | DALI |
| **Primary nominal voltage** | 120-277V ~50/60 Hz |
| **Secondary power / voltage** | 1000 mA |
| **Safety class** | I |
| **Wattage** | 43 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Level of inrush current** | 30 A |
| **Duration of inrush current** | 30 µs |
| **Lumen** | 3100 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 90 ° |
| **Color** | white |
| **CRI** | 80 |
| **UGR ≤** | 19 |
| **Service life** | 30000 h |
| **Length** | 119.5 cm |
| **Width** | 29.5 cm |
| **Height** | 5 cm |

| | |
|---|---|
| 916537 |  |

| | |
|---|---|
| **Net weight** | 4.546 kg |
| **Gross weight** | 5.489 kg |