




# L-LINE OUT WL

**Outdoor LED wall-mounted light anthracite CCT switch 3000/4000 K**

With its linear light variety, the L-LINE OUT family lights the way outdoors. Despite their individual differences, the individual members speak a common language of form, encapsulated in the clean lines of the letter "L". As far as lighting technology is concerned, there are no compromises: the CCT switch for easy selection of light colour temperature (3000 or 4000 K) prior to installation), the straightforward installation process, and a protection rating of IP 65 are just some of the features that make the L-LINE OUT surface-mounted wall light a winner.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1003539 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP65 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Number of through-wires** | 10 |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 350 mA |
| **Safety class** | I |
| **Wattage** | 7 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 45 °C |
| **Level of inrush current** | 10 A |
| **Duration of inrush current** | 40 µs |
| **Lumen** | 500/570 lm |
| **Colour temperature** | 3000/4000 Kelvin |
| **Color** | anthracite |
| **CRI** | 80 |
| **Service life** | 30000 h |
| **Risk Group** | 0 |
| **Width** | 15 cm |
| **Height** | 10 cm |

| | |
|---|---|
| 916406 |  |

| | |
|---|---|
| **Depth** | 10 cm |
| **Net weight** | 1.024 kg |
| **Gross weight** | 1.237 kg |
| **BIG WHITE Page** | 921 |