



NUMINOS® MOVE M | DL

NUMINOS® MOVE DL M, Indoor LED recessed ceiling light white/white 2700 K 40° rotating and pivoting

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® MOVE DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 17.55 watts, luminous flux of 1600 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



Light source

791800	A G E

Item no.	1003569
Lamps included	No
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Secondary power / voltage	500 mA
Safety class	III
Wattage	18 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	40°
Color	white/white
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50 000 h
Risk Group	1
Height	9 cm
Diameter	13.5 cm
Net weight	0.38 kg
Gross weight	0.44 kg
Shape of cut-out	round
Installation depth	10 cm
Installation diameter	12 cm

Accessories

1004790	NUMINOS® M, diffuser Ellipse
1004791	NUMINOS® M, diffuser Prisma
1004792	NUMINOS® M, diffuser Frosted
1004793	NUMINOS® M, diffuser Wabe
1004064	LED driver, 21-29.5 W 500/600/700 mA
1004054	LED driver, 20 W 500 mA PHASE
1004069	LED driver, 29 W 500 mA DALI
1006143	Numinos® M Reducing ring, round 240/120 mm black
1006144	Numinos® M Reducing ring, round 240/120 mm white
1006145	Numinos® M Reducing ring, square 240/120 mm black
1006146	Numinos® M Reducing ring, square 240/120 mm white
1006459	LED bridge driver, 42 W, 500 mA for NUMINOS®, including radio interface for RF module, DALI
1006199	RF module Zigbee for DALI LED bridge driver, single colour
1006454	RF module Casambi for LED bridge driver, single colour