


# NUMINOS® MOVE L | DL

**NUMINOS® MOVE DL L, Indoor LED recessed ceiling light white/black 2700 K 20° rotating and pivoting**

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® MOVE DL L recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 25.41 watts, a luminous flux of 2150 lumens, a colour temperature of 2700 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.




## Light source

| | |
|---|---|
| 791800 | A G E |

| | |
|---|---|
| Item no. | 1003637 |
| Lamps included | No |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| IP Code | IP20 |
| Impact resistance class | IK02 |
| Impact resistance | 0.2 Joule |
| Secondary power / voltage | 700 mA |
| Safety class | III |
| Wattage | 25 W |
| Minimum ambient temperature | -20°C |
| Maximum ambient temperature | 40°C |
| Beam angle | 20° |
| Color | white/black |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| Service life | 50 000 h |
| Risk Group | 1 |
| Height | 9.5 cm |
| Diameter | 16 cm |
| Net weight | 0.52 kg |
| Gross weight | 0.65 kg |
| Shape of cut-out | round |
| Installation depth | 10,5 cm |
| Installation diameter | 14.5 cm |

## Accessories

| | |
|---|---|
| **1004794** | NUMINOS® L, diffuser Ellipse |
| **1004795** | NUMINOS® L, diffuser Prisma |
| **1004796** | NUMINOS® L, diffuser Frosted |
| **1004797** | NUMINOS® L, diffuser Wabe |
| **1004062** | LED driver, 21-29.5 W 500/600/700 mA for Numinos Downlight Serie |
| **1004065** | LED driver, 30 W 700 mA |
| **1004070** | LED driver, 40 W 700 mA DALI |
| **1006147** | Numinos® L Reducing ring, round 240/150 mm black |
| **1006148** | Numinos® L Reducing ring, round 240/150 mm white |
| **1006149** | Numinos® L Reducing ring, square 240/150 mm black |
| **1006150** | Numinos® L Reducing ring, square 240/150 mm white |
| **1006460** | LED bridge driver, 42 W, 700 mA for NUMINOS®, including radio interface for RF module, DALI |
| **1006199** | RF module Zigbee for DALI LED bridge driver, single colour |
| **1006454** | RF module Casambi for LED bridge driver, single colour |