




NUMINOS® MOVE L | DL

NUMINOS® MOVE DL L, Indoor LED recessed ceiling light black/black 3000 K 55° rotating and pivoting

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® MOVE DL L recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 25.41 watts, luminous flux of 2150 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



Light source

791822	A E

Item no.	1003655
Lamps included	No
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Secondary power / voltage	700 mA
Safety class	III
Wattage	25 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	55°
Color	black/black
CRI	90
UGR ≤	25
LXXBXX data	L80B50
Service life	50 000 h
Risk Group	1
Height	9.5 cm
Diameter	16 cm
Net weight	0.52 kg
Gross weight	0.65 kg
Shape of cut-out	round
Installation depth	10,5 cm
Installation diameter	14.5 cm

Accessories

1004794	NUMINOS® L, diffuser Ellipse
1004795	NUMINOS® L, diffuser Prisma
1004796	NUMINOS® L, diffuser Frosted
1004797	NUMINOS® L, diffuser Wabe
1004062	LED driver, 21-29.5 W 500/600/700 mA for Numinos Downlight Serie
1004065	LED driver, 30 W 700 mA
1004070	LED driver, 40 W 700 mA DALI
1006147	Numinos® L Reducing ring, round 240/150 mm black
1006148	Numinos® L Reducing ring, round 240/150 mm white
1006149	Numinos® L Reducing ring, square 240/150 mm black
1006150	Numinos® L Reducing ring, square 240/150 mm white
1006460	LED bridge driver, 42 W, 700 mA for NUMINOS®, including radio interface for RF module, DALI
1006199	RF module Zigbee for DALI LED bridge driver, single colour
1006454	RF module Casambi for LED bridge driver, single colour