



# NUMINOS® MOVE DL XL

**Indoor LED recessed ceiling light black/chrome 3000K 40° rotating and pivoting**

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® MOVE DL XL, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 37.4 watts, luminous flux of 3500 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1003726 |
| **Number of different light outlets** | 1 |
| **Rotating or tilting** | rotary Bar and tiltable |
| **IP Code** | IP 20 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 1050 mA |
| **Safety class** | III |
| **Wattage** | 37.4 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Lumen** | 3500 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 40 ° |
| **Color** | black |
| **CRI** | 90 |
| **UGR ≤** | 19 |
| **LXXBXX data** | L80B50 |
| **Service life** | 50000 h |
| **Light distribution** | rotational symmetric |

| | |
|---|---|
| 791823 |  |

## Accessories

| | |
|---|---|
| 1006152 | Numinos® XL Reducing ring , round 240/180mm white |
| 1006151 | Numinos® XL Reducing ring , round 240/180mm black |
| 1004800 | NUMINOS® XL , diffuser Frosted |
| 1004071 | LED driver 4.2-50W 1050mA DALI |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006154 | Numinos® XL Reducing ring , square 240/180mm white |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1004798 | NUMINOS® XL , diffuser Ellipse |
| 1006153 | Numinos® XL Reducing ring , square 240/180mm black |
| 1004059 | LED driverm 40W multi mA |
| 1006461 | LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004066 | LED driver , 28-40W 1000mA PHASE |
| 1004801 | NUMINOS® XL , diffuser Wabe |
| 1004799 | NUMINOS® XL , diffuser Prisma |

| | |
|---|---|
| **Light outlet** | direct |
| **Risk Group** | 1 |
| **Height** | 11.8 cm |
| **Diameter** | 19 cm |
| **Net weight** | 0.7 kg |
| **Gross weight** | 0.89 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 13 cm |
| **Installation diameter** | 17.5 cm |
| **BIG WHITE Page** | 87 |