

NUMINOS® MOVE DL XL

Indoor LED recessed ceiling light black/chrome 4000K 40° rotating and pivoting

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® MOVE DL XL, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 37.4 watts, luminous flux of 3750 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1003750
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	1050 mA
Safety class	III
Wattage	37.4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	3750 lm
Colour temperature	4000 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric

791850	

Accessories

1006152	Numinos® XL Reducing ring , round 240/180mm white
1006151	Numinos® XL Reducing ring , round 240/180mm black
1004800	NUMINOS® XL , diffuser Frosted
1004071	LED driver 4.2-50W 1050mA DALI
1006454	RF module Casambi for LED bridge driver , single colour
1006154	Numinos® XL Reducing ring , square 240/180mm white
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1004798	NUMINOS® XL , diffuser Ellipse
1006153	Numinos® XL Reducing ring , square 240/180mm black
1004059	LED driverm 40W multi mA
1006461	LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI
1004066	LED driver , 28-40W 1000mA PHASE
1004801	NUMINOS® XL , diffuser Wabe
1004799	NUMINOS® XL , diffuser Prisma

Light outlet	direct
Risk Group	1
Height	11.8 cm
Diameter	19 cm
Net weight	0.7 kg
Gross weight	0.89 kg
Shape of cut-out	round
Installation depth	13 cm
Installation diameter	17.5 cm
BIG WHITE Page	87