

# NUMINOS® DL S

**Indoor LED recessed ceiling light black/black 2700K 20° including leaf springs**

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® DL S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create unobtrustive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 8.6 watts, luminous flux of 670 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1003769 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP 20 / IP 44 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 250 mA |
| **Safety class** | III |
| **Wattage** | 8.6 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Lumen** | 670 lm |
| **Colour temperature** | 2700 Kelvin |
| **Beam angle** | 20 ° |
| **Color** | black |
| **CRI** | 90 |
| **UGR ≤** | 19 |
| **LXXBXX data** | L80B50 |
| **Service life** | 50000 h |
| **Light distribution** | rotational symmetric |
| **Light outlet** | direct |

| | |
|---|---|
| 791819 |  |

## Accessories

| | |
|---|---|
| 1006136 | Numinos® XS Reducing ring , round 160/70mm white |
| 1006458 | LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI |
| 1006135 | Numinos® XS Reducing ring , round 160/70mm black |
| 1004789 | NUMINOS® S , diffuser Wabe |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1004058 | LED driver , 6.5-10W 250mA |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1006137 | Numinos® XS Reducing ring , square 160/70mm black |
| 1006138 | Numinos® XS Reducing ring , square 160/70mm white |
| 1004055 | LED driver , 6.5-10W 250mA PHASE |

| | |
|---|---|
| **Risk Group** | 1 |
| **Height** | 5.2 cm |
| **Diameter** | 8 cm |
| **Net weight** | 0.16 kg |
| **Gross weight** | 0.2 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 5.5 cm |
| **Installation diameter** | 6.8 cm |
| **BIG WHITE Page** | 87 |