

NUMINOS® DL S

Indoor LED recessed ceiling light black/chrome 3000K 20° gimballed, rotating and pivoting, including leaf springs

The NUMINOS light system from SLV skilfully combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® DL S recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light can convince with a power consumption of 8.6 watts, luminous flux of 700 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1003795
Number of different light outlets	1
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	250 mA
Safety class	III
Wattage	8.6 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct

791815	

Accessories

1006136	Numinos® XS Reducing ring , round 160/70mm white
1006458	LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI
1006135	Numinos® XS Reducing ring , round 160/70mm black
1004789	NUMINOS® S , diffuser Wabe
1004067	LED driver , 15W 250mA DALI
1004788	NUMINOS® S , diffuser Frosted
1004787	NUMINOS® S , diffuser Prisma
1004786	NUMINOS® S , diffuser Ellipse
1006454	RF module Casambi for LED bridge driver , single colour
1004058	LED driver , 6.5-10W 250mA
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006137	Numinos® XS Reducing ring , square 160/70mm black
1006138	Numinos® XS Reducing ring , square 160/70mm white
1004055	LED driver , 6.5-10W 250mA PHASE

Risk Group	1
Height	5.2 cm
Diameter	8 cm
Net weight	0.16 kg
Gross weight	0.2 kg
Shape of cut-out	round
Installation depth	5.5 cm
Installation diameter	6.8 cm
BIG WHITE Page	87