



NUMINOS® DL S

Indoor LED recessed ceiling light black/white 3000K 40° gimballed, rotating and pivoting, including leaf springs

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® DL S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 8.6 watts, luminous flux of 730 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1003797
Number of different light outlets	1
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	250 mA
Safety class	III
Wattage	8.6 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	730 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct

791815	

Accessories

1006136	Numinos® XS Reducing ring , round 160/70mm white
1006458	LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI
1006135	Numinos® XS Reducing ring , round 160/70mm black
1004789	NUMINOS® S , diffuser Wabe
1004067	LED driver , 15W 250mA DALI
1004788	NUMINOS® S , diffuser Frosted
1004787	NUMINOS® S , diffuser Prisma
1004786	NUMINOS® S , diffuser Ellipse
1006454	RF module Casambi for LED bridge driver , single colour
1004058	LED driver , 6.5-10W 250mA
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006137	Numinos® XS Reducing ring , square 160/70mm black
1006138	Numinos® XS Reducing ring , square 160/70mm white
1004055	LED driver , 6.5-10W 250mA PHASE

Risk Group	1
Height	5.2 cm
Diameter	8 cm
Net weight	0.16 kg
Gross weight	0.2 kg
Shape of cut-out	round
Installation depth	5.5 cm
Installation diameter	6.8 cm
BIG WHITE Page	87