


NUMINOS® S | DL

NUMINOS® DL S, Indoor LED recessed ceiling light white/chrome 3000 K 20° gimballed, rotating and pivoting, including leaf springs

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® DL S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light can convince with a power consumption of 8.6 watts, luminous flux of 700 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



Light source

791815	A G E

Item no.	1003807
Lamps included	No
Number of different light outlets	1
IP Code	IP20/IP44
Impact resistance class	IK02
Impact resistance	0.2 Joule
Secondary power / voltage	250 mA
Safety class	III
Wattage	9 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	20°
Color	white/chrome
CRI	90
UGR ≤	19
LXXBXX data	L80B50
Service life	50 000 h
Risk Group	1
Height	5.2 cm
Diameter	8 cm
Net weight	0.17 kg
Gross weight	0.19 kg
Shape of cut-out	round
Installation depth	5,5 cm
Installation diameter	6.8 cm

Accessories

1004786	NUMINOS® S, diffuser Ellipse
1004787	NUMINOS® S, diffuser Prisma
1004788	NUMINOS® S, diffuser Frosted
1004789	NUMINOS® S, diffuser Wabe
1004058	LED driver, 6.5-10 W 250 mA
1004055	LED driver, 6.5-10 W 250 mA PHASE
1004067	LED driver, 20 W 250 mA DALI
1006135	Numinos® XS Reducing ring, round 160/70 mm black
1006136	Numinos® XS Reducing ring, round 160/70 mm white
1006137	Numinos® XS Reducing ring, square 160/70 mm black
1006138	Numinos® XS Reducing ring, square 160/70 mm white
1006458	LED bridge driver, 12 W, 250 mA for NUMINOS®, including radio interface for RF module, DALI
1006199	RF module Zigbee for DALI LED bridge driver, single colour
1006454	RF module Casambi for LED bridge driver, single colour