

NUMINOS® DL M

Indoor LED recessed ceiling light black/white 4000K 20°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® DL M recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 17.55 watts, luminous flux of 1750 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1003890
Number of different light outlets	1
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17.55 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1750 lm
Colour temperature	4000 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct

791825	

Accessories

1004792	NUMINOS® M , diffuser Frosted
1004069	LED driver , 29W 500mA
1004064	LED driver , 21-29.5W 500/600/700mA
1006459	LED bridge driver , 42W, 500mA for NUMINOS®, including radio interface for RF module, DALI
1004054	LED driver , 20W 500mA PHASE
1006139	Numinos® S Reducing ring , round 160/100mm black
1006454	RF module Casambi for LED bridge driver , single colour
1004793	NUMINOS® M , diffuser Wabe
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006140	Numinos® S Reducing ring , round 160/100mm white
1006142	Numinos® S Reducing ring , square 160/100mm white
1004790	NUMINOS® M , diffuser Ellipse
1004791	NUMINOS® M , diffuser Prisma
1006141	Numinos® S Reducing ring , square 160/100mm black

Risk Group	1
Height	6.8 cm
Diameter	10.5 cm
Net weight	0.24 kg
Gross weight	0.28 kg
Shape of cut-out	round
Installation depth	7.5 cm
Installation diameter	9 cm
BIG WHITE Page	87