


NUMINOS® M | DL

NUMINOS® DL M, Indoor LED recessed ceiling light white/black 4000 K 20°

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. This also includes NUMINOS® DL M, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light can convince with a power consumption of 17.55 watts, luminous flux of 1600 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



Light source

791825	A G E

Item no.	1003901
Lamps included	No
Number of different light outlets	1
IP Code	IP20/IP44
Impact resistance class	IK02
Impact resistance	0.2 Joule
Secondary power / voltage	500 mA
Safety class	III
Wattage	18 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	20°
Color	white/black
CRI	90
UGR ≤	19
LXXBXX data	L80B50
Service life	50 000 h
Risk Group	1
Height	6.8 cm
Diameter	10.5 cm
Net weight	0.24 kg
Gross weight	0.28 kg
Shape of cut-out	round
Installation depth	7,5 cm
Installation diameter	9 cm

Accessories

1004790	NUMINOS® M, diffuser Ellipse
1004791	NUMINOS® M, diffuser Prisma
1004792	NUMINOS® M, diffuser Frosted
1004793	NUMINOS® M, diffuser Wabe
1004064	LED driver, 21-29.5 W 500/600/700 mA
1004054	LED driver, 20 W 500 mA PHASE
1004069	LED driver, 29 W 500 mA DALI
1006139	Numinos® S Reducing ring, round 160/90 mm black
1006140	Numinos® S Reducing ring, round 160/90 mm white
1006141	Numinos® S Reducing ring, square 160/90 mm black
1006142	Numinos® S Reducing ring, square 160/90 mm white
1006459	LED bridge driver, 42 W, 500 mA for NUMINOS®, including radio interface for RF module, DALI
1006199	RF module Zigbee for DALI LED bridge driver, single colour
1006454	RF module Casambi for LED bridge driver, single colour