

NUMINOS® DL L

Indoor LED recessed ceiling light black/black 2700K 40°

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® DL L recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 25.41 watts, a luminous flux of 2150 lumens, a colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1003916
Number of different light outlets	1
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	25.41 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	2150 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct

791800	

Accessories

1004062	LED driver , 21-29.5W 500/600/700mA for Numinos Downlight Serie
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1006143	Numinos® M Reducing ring , round 240/120mm black
1006460	LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI
1004794	NUMINOS® L , diffuser Ellipse
1006146	Numinos® M Reducing ring , square 240/120mm white
1006454	RF module Casambi for LED bridge driver , single colour
1006144	Numinos® M Reducing ring , round 240/120mm white
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1004070	LED driver , 40W 700mA DALI
1006145	Numinos® M Reducing ring , square 240/120mm black
1004797	NUMINOS® L , diffuser Wabe
1004065	LED driver , 30W 700mA

Risk Group	1
Height	8.5 cm
Diameter	13 cm
Net weight	0.465 kg
Gross weight	0.525 kg
Shape of cut-out	round
Installation depth	9 cm
Installation diameter	11.7 cm
BIG WHITE Page	87