

# NUMINOS® DL L

**Indoor LED recessed ceiling light white/chrome 2700K 20°**

The NUMINOS light system from SLV perfectly combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® DL L recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 25.41 watts, luminous flux of 2150 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1003927 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP 20 / IP 44 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 700 mA |
| **Safety class** | III |
| **Wattage** | 25.41 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Lumen** | 2150 lm |
| **Colour temperature** | 2700 Kelvin |
| **Beam angle** | 20 ° |
| **Color** | white |
| **CRI** | 90 |
| **UGR ≤** | 19 |
| **LXXBXX data** | L80B50 |
| **Service life** | 50000 h |
| **Light distribution** | rotational symmetric |
| **Light outlet** | direct |

| | |
|---|---|
| 791800 |  |

## Accessories

| | |
|---|---|
| 1004062 | LED driver , 21-29.5W 500/600/700mA for Numinos Downlight Serie |
| 1004795 | NUMINOS® L , diffuser Prisma |
| 1004796 | NUMINOS® L , diffuser Frosted |
| 1006143 | Numinos® M Reducing ring , round 240/120mm black |
| 1006460 | LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004794 | NUMINOS® L , diffuser Ellipse |
| 1006146 | Numinos® M Reducing ring , square 240/120mm white |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006144 | Numinos® M Reducing ring , round 240/120mm white |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1004070 | LED driver , 40W 700mA DALI |
| 1006145 | Numinos® M Reducing ring , square 240/120mm black |
| 1004797 | NUMINOS® L , diffuser Wabe |
| 1004065 | LED driver , 30W 700mA |

| | |
|---|---|
| **Risk Group** | 1 |
| **Height** | 8.5 cm |
| **Diameter** | 13 cm |
| **Net weight** | 0.465 kg |
| **Gross weight** | 0.525 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 9 cm |
| **Installation diameter** | 11.7 cm |
| **BIG WHITE Page** | 87 |