


NUMINOS® L | DL

NUMINOS® DL L, Indoor LED recessed ceiling light white/black 3000 K 40°

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® DL L recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create unobtrustive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 25.41 watts, luminous flux of 2150 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



Light source

791822	A G E

Item no.	1003952
Lamps included	No
Number of different light outlets	1
IP Code	IP20/IP44
Impact resistance class	IK02
Impact resistance	0.2 Joule
Secondary power / voltage	700 mA
Safety class	III
Wattage	25 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	40°
Color	white/black
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50 000 h
Risk Group	1
Height	8.5 cm
Diameter	13 cm
Net weight	0.47 kg
Gross weight	0.54 kg
Shape of cut-out	round
Installation depth	9 cm
Installation diameter	11.7 cm

Accessories

1004794	NUMINOS® L, diffuser Ellipse
1004795	NUMINOS® L, diffuser Prisma
1004796	NUMINOS® L, diffuser Frosted
1004797	NUMINOS® L, diffuser Wabe
1004062	LED driver, 21-29.5 W 500/600/700 mA for Numinos Downlight Serie
1004065	LED driver, 30 W 700 mA
1004070	LED driver, 40 W 700 mA DALI
1006143	Numinos® M Reducing ring, round 240/120 mm black
1006144	Numinos® M Reducing ring, round 240/120 mm white
1006145	Numinos® M Reducing ring, square 240/120 mm black
1006146	Numinos® M Reducing ring, square 240/120 mm white
1006460	LED bridge driver, 42 W, 700 mA for NUMINOS®, including radio interface for RF module, DALI
1006199	RF module Zigbee for DALI LED bridge driver, single colour
1006454	RF module Casambi for LED bridge driver, single colour