

NUMINOS® DL XL

Indoor LED recessed ceiling light white/white 2700K 55°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® DL XL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 37.4 watts, luminous flux of 3500 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

Item no.	1004004
Number of different light outlets	1
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	1050 mA
Safety class	III
Wattage	37.4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	3500 lm
Colour temperature	2700 Kelvin
Beam angle	55 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct

791857	

Accessories

1006148	Numinos® L Reducing ring , round 240/150mm white
1006149	Numinos® L Reducing ring , square 240/150mm black
1004800	NUMINOS® XL , diffuser Frosted
1004071	LED driver 4.2-50W 1050mA DALI
1006150	Numinos® L Reducing ring , square 240/150mm white
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006147	Numinos® L Reducing ring , round 240/150mm black
1004798	NUMINOS® XL , diffuser Ellipse
1004059	LED driverm 40W multi mA
1006461	LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI
1004066	LED driver , 28-40W 1000mA PHASE
1004801	NUMINOS® XL , diffuser Wabe
1004799	NUMINOS® XL , diffuser Prisma

Risk Group	1
Height	10.8 cm
Diameter	16 cm
Net weight	0.715 kg
Gross weight	0.87 kg
Shape of cut-out	round
Installation depth	11.5 cm
Installation diameter	14.5 cm
BIG WHITE Page	87