


# NUMINOS® S CW

**PHASE, Surface-mounted ceiling light, 4000 K, 8 Watt, trailing edge, 36°, matt white / matt black**

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® CW, PHASE LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Deckenaufbauleuchte The luminaire impresses with a luminous flux of 1100 lm and an impressive efficiency of 137.50 lm/W. Their colour temperature of 4000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1004119 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP20 |
| **Assembly** | Surface |
| **Assembly details** | Ceiling,Wall |
| **Dimmable** | Yes |
| **Dimming technology** | trailing edge |
| **Number of through-wires** | 128 |
| **Primary nominal voltage** | 220-240AC50/60 Hz |
| **Secondary power / voltage** | 200 |
| **Safety class** | I |
| **Wattage** | 8 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 45 °C |
| **Number of luminaires at LS B16A** | 128 |
| **Number of luminaires at LS C16A** | 128 |
| **Level of inrush current** | 10 A |
| **Duration of inrush current** | 50 µs |
| **Lumen** | 1100 lm |
| **Colour temperature** | 4000 Kelvin |
| **Beam angle** | 36 ° |
| **Color** | matt white/matt black |

| | |
|---|---|
| 1411582 |  |

| | |
|---|---|
| **CRI** | 90 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Length** | 16.2 cm |
| **Height** | 14.5 cm |
| **Diameter** | 6.5 cm |
| **Net weight** | 0.577 kg |
| **Gross weight** | 0.883 kg |
| **BIG WHITE Page** | 337 |