




NUMINOS® M | 3Ph., PHASE

NUMINOS® M 3Ph., PHASE, 3~ Spotlight, cylindrical, 3000 K, 14 Watt, trailing edge, 36°, matt white / matt black

The NUMINOS® M 3Ph. PHASE is a cylindrical 3-phase spotlight designed for mounting on ceiling track systems. It is suitable for indoor use, for example in commercial or public areas where targeted lighting is required. The luminaire operates at a power of 14 watts and produces a luminous flux of 1800 lumens with a colour temperature of 3000 Kelvin and a beam angle of 36 degrees. The housing is made of aluminium and is available in matt white or matt black. Control is via trailing edge phase-cut dimming. The product has an IP20 protection rating and measures 18.5 cm in length, 8.5 cm in diameter, and 15.5 cm in height. The declared service life is 50,000 hours.



Light source

2093861	A D

Item no.	1004183
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Track
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	78.0
Number of luminaires at LS C16A	78.0
Level of inrush current	10 A
Duration of inrush current	50 µs
Beam angle	36°
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	18.5 cm
Height	15.5 cm
Diameter	8.5 cm
Net weight	0.78 kg

Accessories

1006168	NUMINOS® M, white front ring
1008145	NUMINOS® M, front ring, matt gold
1008141	NUMINOS® M, front ring, matt copper