




NUMINOS® L | 3Ph., PHASE

NUMINOS® L 3Ph., PHASE, 3~ Spotlight, cylindrical, 2700 K, 20 Watt, trailing edge, 36°, matt black

The NUMINOS® L 3Ph. is a cylindrical 3-phase spot designed for mounting on ceiling track systems. It is particularly suitable for indoor use where directional lighting is required. With a power consumption of 20 watts, the spot produces a luminous flux of 2300 lumens at a warm white colour temperature of 2700 Kelvin and a beam angle of 36 degrees. The housing is made of aluminium and finished in matte black. Dimming is achieved via phase-cut control. The spot measures 21.3 cm in length, 10 cm in diameter, and 17 cm in height. The IP20 rating provides basic protection against contact and solid foreign objects.



Light source

2093865	A G D

Item no.	1004267
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Track
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	78.0
Number of luminaires at LS C16A	78.0
Level of inrush current	10 A
Duration of inrush current	50 µs
Beam angle	36°
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	21.3 cm
Height	17 cm
Diameter	10 cm
Net weight	1.09 kg

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper