


NUMINOS® L | CL, PHASE

NUMINOS® L CL, PHASE, Surface-mounted ceiling light, 3000 K, 20 Watt, trailing edge, 36°, matt white / matt black

The NUMINOS® L SPOT is a ceiling surface-mounted luminaire with a cylindrical shape, suitable for indoor use. It features a light colour of 3000 K and a luminous flux of 2400 lumens at a power consumption of 20 watts. The beam angle is 36°, allowing for targeted illumination. The housing is made of aluminium and polycarbonate, ensuring a robust construction. The luminaire is equipped with phase-cut dimming, enabling stepless adjustment of light intensity. With an IP20 protection rating, it is suitable for dry indoor areas. The dimensions are 21.3 cm in length, 10 cm in diameter, and 18 cm in height. The luminaire is available in matt white or matt black.



Light source

2093861	A G D

Item no.	1004303
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	78
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	78.0
Number of luminaires at LS C16A	78.0
Level of inrush current	10 A
Duration of inrush current	50 µs
Beam angle	36°
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper