


NUMINOS® M CL

DALI, Surface-mounted ceiling light, 3000 K, 13 Watt, DALI, 60°, matt white / matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® CL, DALI LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Deckenaufbauleuchte The luminaire impresses with a luminous flux of 1800 lm and an impressive efficiency of 138.46 lm/W. Their colour temperature of 3000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

Item no.	1004520
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI,Touch
Number of through-wires	94
Primary nominal voltage	200-240AC50/60 Hz
Secondary power / voltage	350
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Number of luminaires at LS B16A	94
Number of luminaires at LS C16A	94
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Lumen	1800 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	matt white/matt black

1411586	

CRI	90
Service life	50000 h
Risk Group	1
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.726 kg
Gross weight	0.991 kg
BIG WHITE Page	185