




NUMINOS® L | 3Ph., DALI

NUMINOS® L 3Ph., DALI, 3~ Spotlight, cylindrical, 3000 K, 19 Watt, DALI, 36°, matt black

The NUMINOS® L 3Ph. DALI 3~ spot is a cylindrical spotlight designed for mounting on ceiling track systems. It is particularly suitable for indoor use where directional lighting is required. The spot delivers a luminous flux of 2400 lumens at a colour temperature of 3000 K and a beam angle of 36°. The power consumption is 19 watts. The housing is made of aluminium with a matt black finish. With a length of 21.3 cm, a diameter of 10 cm, and a height of 18 cm, the device is compactly designed. The IP20 protection rating allows use in protected indoor areas. Dimming is controlled via DALI 2 and touch technology, enabling flexible light management. The declared service life is 50,000 hours.



Light source

2093861	A G D

Item no.	1004563
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Track
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALITouch
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	94.0
Number of luminaires at LS C16A	94.0
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Beam angle	36°
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm
Net weight	1.14 kg

Accessories

1006169	NUMINOS® L, white front ring
1008146	NUMINOS® L, front ring, matt gold
1008142	NUMINOS® L, front ring, matt copper