




OCULUS DL MOVE

Indoor LED wall and ceiling mounted light black DIM-TO-WARM 2000-3000 K

With a high colour rendering index (CRI >90) and the option of dim-to-warm dimming for an especially warm light (2000-3000 K), every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting.



TECHNICAL DATA

Item no.	1004668
Number of different light outlets	1
Rotating or tilting	tiltable
IP Code	IP20
Dimmable	Yes
Dimming technology	Dim-to-Warm,trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	250 mA
Safety class	II
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	2 A
Duration of inrush current	50 µs
Lumen	36-780 lm
Colour temperature	2000-3000 Kelvin
Beam angle	100 °
Color	black
CRI	90
Service life	25000 h
Risk Group	1
Height	7.3 cm

916608	

Diameter	12 cm
Net weight	0.565 kg
Gross weight	0.776 kg
Shape of cut-out	round
Installation depth	8 cm
Installation diameter	10.8 cm
BIG WHITE Page	147