




# PANEL TRACK round 200 mm

**1-phase spot, black, 18 W 3000 K**

With the modern and space-saving PANEL, you provide efficient basic lighting. A pleasant, homogeneous and glare-free light is produced by the 1-phase system light LED with 1,800 lumen and 3,000 Kelvin. The light is made of polycarbonate (PC) and steel and has a long LED lifespan of 50,000 hours. Experience light with SLV – your reliable partner for all kinds of indoor lights for 40 years.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1004935 |
| **Number of different light outlets** | 1 |
| **Rotating or tilting** | rotary bar and tiltable |
| **IP Code** | IP20 |
| **Impact resistance** | 0.2 Joule |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 450 mA |
| **Safety class** | II |
| **Wattage** | 18 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Level of inrush current** | 15 A |
| **Duration of inrush current** | 20 µs |
| **Lumen** | 1800 lm |
| **Colour temperature** | 3000 Kelvin |
| **Color** | black |
| **CRI** | 90 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Length** | 23.1 cm |
| **Width** | 20 cm |
| **Height** | 11.05 cm |

| | |
|---|---|
| 916407 |  |

| | |
|---|---|
| **Net weight** | 0.446 kg |
| **Gross weight** | 0.602 kg |
| **BIG WHITE Page** | 589 |