


# NUMINOS® XL CL

**DALI, Surface-mounted ceiling light, 4000 K, 27 Watt, DALI, 36°, matt white / matt black**

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® CL, DALI LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Deckenaufbauleuchte The luminaire impresses with a luminous flux of 3900 lm and an impressive efficiency of 144.44 lm/W. Their colour temperature of 4000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1005757 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP20 |
| **Assembly** | Surface |
| **Assembly details** | Ceiling |
| **Dimmable** | Yes |
| **Dimming technology** | DALI,Touch |
| **Number of through-wires** | 58 |
| **Primary nominal voltage** | 200-240AC50/60 Hz |
| **Secondary power / voltage** | 700 |
| **Safety class** | I |
| **Wattage** | 27 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 50 °C |
| **Number of luminaires at LS B16A** | 58 |
| **Number of luminaires at LS C16A** | 58 |
| **Level of inrush current** | 2.825 A |
| **Duration of inrush current** | 188 µs |
| **Lumen** | 3900 lm |
| **Colour temperature** | 4000 Kelvin |
| **Beam angle** | 36 ° |
| **Color** | matt white/matt black |

| | |
|---|---|
| 1411588 |  |

| | |
|---|---|
| **CRI** | 90 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Length** | 25.8 cm |
| **Height** | 20 cm |
| **Diameter** | 12 cm |
| **Net weight** | 1.59 kg |
| **Gross weight** | 2.024 kg |
| **BIG WHITE Page** | 343 |