

NUMINOS® ZOOM M PHASE

white 3-phase spot, 20W 2700K 15-60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® ZOOM M PHASE 3-phase system light LED, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1006109
Rotating or tilting	rotary bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Stroboscopic effect (SVM)	0.03
Lumen	680-1650 lm
Colour temperature	2700 Kelvin
Beam angle	15 °
Color	white
CRI	90
UGR ≤	25
LXXBXX data	L70B50
Service life	40000 h
Risk Group	1
Length	19 cm

791800	

Height	16.5 cm
Diameter	8.5 cm
Net weight	0.989 kg
Gross weight	1.294 kg
BIG WHITE Page	115