

M-POL 90 Pole

Bollard, anthracite, 83.4cm

DALI-compatible bollard light for professional outdoor projects: the aluminium M-POL 90 Pole can be dimmed and controlled via the digital interface. Variable lamp heads and diffusers ensure a wide range of applications. The colour temperature (2700/3000K) can be selected via the CCT switch before installation. Thanks to its IP65 protection class rating, this anthracite bollard light is protected against jets of water from all directions. To ensure it can withstand heavy impacts, it has an IK10 impact rating. Easy installation via the connection box is entirely straightforward.

TECHNICAL DATA

Item no.	1006381
Color	matt anthracite
Height	83.4 cm
Diameter	12.4 cm
Net weight	2.995 kg
Gross weight	3.815 kg
BIG WHITE Page	614

Accessories

1006387	M-POL S Polehead , Shader lamp head, anthracite, 11W, 285/310lm, 2700/3000K, CRI90
1006383	M-POL M Polehead , Lamp head, anthracite, 11W, 470/510lm, 2700/3000K, CRI90
1006388	M-POL M Polehead , Shader lamp head, anthracite, 11W, 420/460lm, 2700/3000K, CRI90
1006392	M-POL M Polehead , Louver lamp head, anthracite, 19W, 350/370lm, 2700/3000K, CRI90, DALI
1006390	M-POL M Polehead , Lamp head, anthracite, 19W, 1150/1230lm, 2700/3000K, CRI90, DALI
1006453	Y-CONNECTION BOX , 5-pin, IP68, black, DALI
228726	Y-CONNECTION BOX , black, IP68
228730	CONNECTION BOX , 3-pin, IP68
1006389	M-POL S Polehead , Lamp head, anthracite, 19W, 890/950lm, 2700/3000K, CRI90, DALI
1006384	M-POL M Polehead , Lamp head, anthracite, 11W, 590/660lm, 2700/3000K, CRI90
1006393	M-POL S Polehead , Shader lamp head, anthracite, 19W, 520/550lm, 2700/3000K, CRI90, DALI

1006391	M-POL S Polehead , Louver lamp head, anthracite, 19W, 260/270lm, 2700/3000K, CRI90, DALI
1006394	M-POL M Polehead , Shader lamp head, anthracite, 19W, 820/870lm, 2700/3000K, CRI90, DALI
1006385	M-POL S Polehead , Louver lamp head, anthracite, 11W, 145/155lm, 2700/3000K, CRI90
1006386	M-POL M Polehead , Louver lamp head, anthracite, 11W, 190/210lm, 2700/3000K, CRI90
1006382	M-POL ground anchor , stainless steel