
# MEDO® PRO 30

**wall- and ceiling-mounted light, round, 3000/4000K, 10W, DALI, Touch, 70°, UGR<19, DC, white**

With MEDO® PRO DC, you benefit from all the technical advantages of the prismatic MEDO® PRO version with UGR<19. It is DALI controllable and impresses with its service life of L80B10@50,000h, eligible energy efficiency from 120 lm/W and a higher indirect light component. Efficiency is also the order of the day when it comes to installation, which is particularly fast thanks to our EasyBase. The improved protection code IP50 and an outstanding CRI>90 colour reproduction index ensure exceptional quality. Two elegant casing colours and a CCT switch that enables you to choose between 3000 K and 4000 K lets you personalise your lighting situation. In addition, you can be sure that the MEDO® PRO DC lights will continue to shine groundbreakingly even if the power supply fails, thanks to the integrated DC driver.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1006412 |
| **IP Code** | IP 50 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly** | Surface |
| **Assembly details** | Ceiling,Ceiling with Acc.,Wall |
| **Dimmable** | Yes |
| **Dimming technology** | DALI,Touch |
| **Primary nominal voltage** | 220-240V ~50/60Hz |
| **Secondary power / voltage** | 250 mA |
| **Safety class** | I |
| **Wattage** | 10 W |
| **Ambient temperature** | 25 °C |
| **Minimum ambient temperature** | -25 °C |
| **Maximum ambient temperature** | 45 °C |
| **Operating efficiency (LOR)** | 0,83 |
| **Network rated standby power** | 0.2 W |
| **Number of luminaires at LS B16A** | 38 |
| **Number of luminaires at LS C16A** | 64 |
| **Level of inrush current** | 16 A |
| **Duration of inrush current** | 255 µs |
| **Stroboscopic effect (SVM)** | 0.05 |

| | |
|---|---|
| 1807451 |  |

## Accessories

| | |
|---|---|
| 1001952 | MEDO 5m suspension , black |
| 1001950 | MEDO 5m suspension , white |
| 135250 | SUSPENSION SET , for MEDO round pendant, round, black, 5-wire |
| 1001951 | MEDO 5m suspension , silver-grey |
| 135251 | SUSPENSION SET , for MEDO round pendant, round, white, 5-wire |
| 135254 | SUSPENSION SET , for MEDO round pendant, round, silver-grey, 5-wire |

| | |
|---|---|
| **Lumen** | 1250/1250 lm |
| **Colour temperature** | 3000/4000 Kelvin |
| **Beam angle** | 70 ° |
| **Color** | white |
| **CRI** | 90 |
| **UGR ≤** | 19 |
| **LXXBXX data** | L80B10 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 9.2 cm |
| **Diameter** | 28 cm |
| **Net weight** | 1.5 kg |
| **Gross weight** | 1.605 kg |
| **BIG WHITE Page** | 157 |