


NUMINOS DL, MOVE | DL, Move

NUMINOS® PROJECTOR XS, recessed ceiling light, 3000 K, 40°, cylindrical, white / chrome

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700 K/3000 K/4000 K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.



Item no.	1006899
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Secondary power / voltage	200 mA
Safety class	III
Wattage	7 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	40°
Color	white/chrome
UGR ≤	22
LXXBXX data	L80B50
Risk Group	1
Length	8 cm
Diameter	4.9 cm
Net weight	0.28 kg
Gross weight	0.34 kg
Shape of cut-out	round
Installation depth	10 cm
Installation diameter	6.8 cm

Light source

798303	A F

Accessories

1005609	LED Driver, 200 mA 10 W PHASE, Quick Connector
1005610	LED Driver, 200 mA 10 W, Quick Connector
1005611	LED Driver, 200 mA 13,5 W DALI dimmable, Quick Connector
1005612	NUMINOS® XS, diffuser
1005613	NUMINOS® XS, transparent diffuser
1005614	NUMINOS® XS, frosted diffuser
1005615	NUMINOS® XS, black diffuser
1006457	LED bridge driver, 12 W, 200 mA for NUMINOS®, including radio interface for RF module, DALI
1006199	RF module Zigbee for DALI LED bridge driver, single colour
1006454	RF module Casambi for LED bridge driver, single colour