




NUMINOS DL, MOVE | DL, Move

NUMINOS® PROJECTOR S, recessed ceiling light, 2700 K, 40°, cylindrical, black / black

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700 K/3000 K/4000 K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.



Item no.	1006924
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Secondary power / voltage	250 mA
Safety class	III
Wattage	9 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	40°
Color	black/black
UGR ≤	19
LXXBXX data	L80B50
Risk Group	1
Length	12.5 cm
Diameter	6 cm
Net weight	0.54 kg
Gross weight	0.67 kg
Shape of cut-out	round
Installation depth	15 cm
Installation diameter	8.8 cm

Light source

791819	A to G, E

Accessories

1004786	NUMINOS® S, diffuser Ellipse
1004787	NUMINOS® S, diffuser Prisma
1004788	NUMINOS® S, diffuser Frosted
1004789	NUMINOS® S, diffuser Wabe
1004055	LED driver, 6.5-10 W 250 mA PHASE
1004058	LED driver, 6.5-10 W 250 mA
1004067	LED driver, 20 W 250 mA DALI
1006458	LED bridge driver, 12 W, 250 mA for NU-MINOS®, including radio interface for RF module, DALI
1006199	RF module Zigbee for DALI LED bridge driver, single colour
1006454	RF module Casambi for LED bridge driver, single colour