


# NUMINOS® PROJECTOR S

**recessed ceiling light, 3000 K, 20°, cylindrical, white / white**

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700K/3000K/4000K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1006949 |
| **Number of different light outlets** | 1 |
| **Rotating or tilting** | rotary bar and tiltable |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 250 mA |
| **Safety class** | III |
| **Wattage** | 8.6 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Lumen** | 730 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 20 ° |
| **Color** | white |
| **CRI** | 90 |
| **UGR ≤** | 19 |
| **LXXBXX data** | L80B50 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Length** | 12.5 cm |
| **Diameter** | 6 cm |
| **Net weight** | 0.55 kg |

| | |
|---|---|
| 791815 |  |

## Accessories

| | |
|---|---|
| 1006458 | LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004789 | NUMINOS® S , diffuser Wabe |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1004058 | LED driver , 6.5-10W 250mA |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1004055 | LED driver , 6.5-10W 250mA PHASE |

| | |
|---|---|
| **Gross weight** | 0.589 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 15 cm |
| **Installation diameter** | 8.8 cm |
| **BIG WHITE Page** | 92 |