


I-RING

free-standing lamp, 9.2 W, 3000 K, anthracite

Indirect lighting in an organic ring shape summed up: the new I-RING floor light creates flexible and warm-white (3000 K) accented lighting in upmarket outdoor areas thanks to its pivoting and rotatable lamp head. It also prevents light pollution as far as possible. The anthracite-coloured outdoor light is optimally protected thanks to its IP65 rating and features an exceptionally long lifespan of 50,000 hours. A well-rounded lighting experience.



TECHNICAL DATA

Item no.	1007237
Rotating or tilting	rotary bar and tiltable
IP Code	IP65
Impact resistance class	IK 05
Primary nominal voltage	100-240V ~50/60 Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	9.2 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Operating efficiency (LOR)	0.54
Number of luminaires at LS B16A	50
Number of luminaires at LS C16A	80
Level of inrush current	12 A
Duration of inrush current	300 µs
Lumen	670 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	80
Service life	50000 h
Risk Group	0
Height	65 cm

1807467	

Accessories

228753	SCREW SET , stainless steel, M8, incl. cap nuts, plugs and washers

Diameter	24 cm
Net weight	2.313 kg
Gross weight	3.912 kg
BIG WHITE Page	718