




LID II UP/DOWN

wall-mounted light, 2700/3000 K, 28 W, PHASE, 100°, anthracite

Adjustable light colour via CCT switch (2700 K/3000 K), a high colour rendering index of over 80 and a long lifespan of 50,000 hours: the new LID II UP/DOWN wall light emits a powerful light with its upward and downward-facing, pivoting lamp heads which can be adjusted as needed. Simply perfect for atmospheric lighting of pathways, terraces or walls of homes and office buildings.



TECHNICAL DATA

Item no.	1007281
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 03
Impact resistance	0.2 Joule
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	20
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	30
Number of luminaires at LS C16A	30
Level of inrush current	12 A
Duration of inrush current	40 µs
Temperature at glass (light emission)	70 °C
Lumen	750/750 lm
Colour temperature	2700/3000 Kelvin
Beam angle	100 °

1807466	

Color	anthracite
CRI	80
Service life	50000 h
Risk Group	1
Depth	6.5 cm
Diameter	22 cm
Net weight	0.976 kg
Gross weight	1.263 kg
BIG WHITE Page	847