




MEDO® PRO 30 | CW, DALI, UGR<19

MEDO® PRO 30, wall- and ceiling-mounted light, round, 3000/4000 K, 10 W, DALI, Touch, 70°, UGR <19, black

The MEDO® PRO 30 is a ROUND surface-mounted wall and ceiling luminaire designed for indoor use. It delivers a luminous flux of 1250 lumens with selectable colour temperatures of 3000 or 4000 Kelvin and has a power consumption of 10 watts. The luminaire features DALI-2 and touch dimming functions, allowing flexible light control. The housing is made of aluminium and steel, with a diameter of 28 centimetres and a height of 9.2 centimetres. The light distribution has a beam angle of 70 degrees, with a UGR value below 19, ensuring glare-free illumination. Protection rating IP50 and impact resistance according to IK02 provide a robust design suitable for indoor environments.



Light source

1807451	A C

Item no.	1007284
Lamps included	No
Number of different light outlets	2
IP Code	IP50
Impact resistance class	IK02
Impact resistance	0.2 Joule
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	20
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Operating efficiency (LOR)	0.83
Number of luminaires at LS B16A	72.0
Number of luminaires at LS C16A	122.0
Level of inrush current	52 A
Duration of inrush current	1 µs
Beam angle	70°
Color	black/black
CRI	90
UGR ≤	19
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	9.2 cm
Diameter	28 cm

Accessories

135250	SUSPENSION SET, for MEDO round pendant, round, black, 5-wire
135251	SUSPENSION SET, for MEDO round pendant, round, white, 5-wire
1001950	MEDO 5 m suspension, white
1001952	MEDO 5 m suspension, black